

inliten[®]

Change Your Frame Of Mind

Product Focus:

0.8 U-value Triple Glazed Windows

“one of the most energy efficient windows on the market”

Inliten 0.8 Features & Benefits:

- Argon filled units – no need for expensive Krypton gas
- Steel reinforcing – no need for plastic reinforcing
- 40mm mechanically strong and flush-fitting bead; designed for use with Inliten system
- Insulated chambers
- Fitter-friendly 40mm glass unit as standard
- Float/Low E Soft Coat unit
- Glass U-value of only $0.6\text{w/m}^2\text{K}$
- Inliten 70mm System with 50/60mm outer
- Available in full range of Inliten colours
- Certified by independent approved simulator



CAMDEN GROUP	
Inliten 70 - 0.8 model	
Whole Window U-value	0.8
Thermal Transmittance	0.8 $\text{w/m}^2\cdot\text{k}$
Solar Factor	0.25
Air Leakage	0.00 $\text{w/m}^2\cdot\text{k}$
Test Report No: CU11120-28	
Testing Laboratory: Buildcheck	
<small>This document confirms the U-value calculations of the product listed above carried out by Buildcheck in accordance with BS EN 12530 & regulations. Solar Factor and air leakage calculations are therefore indicative results only. Buildcheck are an independent testing agency and do not form a NER scheme. This document cannot be used as evidence of BSRC or other NER scheme registration.</small>	

We can guarantee that when you order an Inliten 0.8 window, then a 0.8 window is what you will actually get!

For more information call the Camden Sales Team on:

UK: 028 9446 2419 ROI: 048 9446 2419

Products manufactured by: Camden Group, 4-7 Steeple Road Industrial Estate, Antrim, Northern Ireland, BT41 1AB

Images for illustration purposes only. All information correct at time of publication. Subject to Camden Group T&Cs.